

NORRIS

BODY STYLE VALVES

MANUFACTURED IN CANADA BY ALBERTA OIL TOOL



ECONOMICAL

VERSATILE

RELIABLE

ISO 9002



Quality Certification
Bureau Inc.
Registered Firm ISO 9002/93-10

Threaded end configuration available in 1 1/2" through 4" sizes. Grooved end body available in 2" through 4" sizes.

Norris Body Style Valves are available with an optional locking device and on-off handle.



Nickle plated, ductile iron disc standard. 360° uninterrupted contact of disc o-ring with seat.

Available with a choice of special o-rings in a wide variety of closely controlled elastomer compounds.

Choice of rugged cast iron or aluminum bodies. Epoxy coated cast iron bodies are also available.

All Norris Body Style Valves feature positive disc drive. As a result assembly and disassembly are simple, making field repairs fast.

Each valve is tested to 110% of its full 175 psi working pressure.



DIM	VALVE SIZE		
	2"	3"	4"
A	4.63	5.75	6.88
B	10.50	10.81	12.13
C	2.50	3.25	3.75
D	6.69	6.88	6.63
E	2.88	4.00	5.00
F	9.94	9.94	9.94
G	3.00	4.13	5.13




Fig. No.	Size	Wt. Lbs.	Body	Shaft	Disc	O-Ring *	Handle
B-101 General Purpose	2"	6	High Tensile strength cast iron ASTM A126	Type 416 Stainless Steel	Aluminum Bronze ASTM B148 Type 316 Stainless Steel Ductile Iron ASTM A395 60 - 40 - 18	Buna N	On-Off Handle with 10 position topworks
	3"	13					
	4"	16					
B-551 Aluminum	2"	3	Aluminum Type 356-T6	Type 416 Stainless Steel	Aluminum Bronze ASTM B148 Type 316 Stainless Steel Ductile Iron ASTM A395 60 - 40 - 18	Buna N	On-Off Handle with 10 position topworks
	3"	5					
	4"	7					

* Optional O-Ring materials:
B - Viton
H - Highly Saturated Nitrile
S - EPDM

E - Black Neoprene
K - Hypalon
Y - Kairrez

F - Atlas
L - ECO

G - White Neoprene
M - Buna N (low temperature)



**ALBERTA
OIL TOOL**

Edmonton, Alberta
9530 - 60 Avenue, T6E 0C1
Phone: (780) 434-8566
Fax: (780) 434-4267
www.albertaoiltool.com

ISSUE DATE: 02/16/01
REVISION: D